

EXCEL.....

SEWING SUPPLY

SNAD[®]



SNap ADhesively Attached

YKK Snap Fasteners America Inc. introduces its plastic adhesive snap components for the marine industry. Unlike traditional metal screw studs used for marine applications, this product will not snag clothing or deteriorate from exposure to sunlight, sand and dirt. Plus, its unique dome shape enables it to be walked on without causing pain.

Applications

- Use wherever a conventional screw stud might be used:
 - Marine carpeting for decks
 - Cushions and seating
 - Canvas for decks, bulkheads or panels
 - Console covers
- Use to replace existing screw studs without the need to fill-in the screw hole.

What's even more amazing about the snap component is how it is secured to boat surfaces. On the underside of the plastic dome is a pad of 3M,[™] VHB[™] acrylic conformable foam adhesive tape that enables the snap to adhere to boat surfaces without having to drill a hole. For more than 20 years the VHB[™] product line has proven to be tough in marine, automotive, medical, aerospace, and architectural applications. YKK has adapted it to use with its patented design to bring flexibility and convenience to the marine industry. All one must do is simply clean the surface to which the snap is to be applied, peel off the protective paper backing, position and firmly hold the snap in place and release.

No tool, no wait, no splits, no hole!

SNAD[®] 40mm Components

Stud and socket are compatible with all other snap components.



ORDER TOLL FREE

TOLL FREE 1-877-322-6544
LOCAL 1-973-249-0430
FAX 1-973-546-4112
WEB excelsewingsupply.com

90 Dayton Avenue, Building 6c, Passaic, NJ 07055 **YKK[®]**
Excel Sewing Supply is an authorized distributor for all YKK Fasteners.





Features:

- Attaches to boat surfaces with adhesive. No hole!
- Very forgiving of DIY'ers.
- 3M™ VHB™ Tape adhesive.
- 45 mils (1.1 mm) conformable tape.
- Domed profile for socket and stud.
- Automotive grade POM with UV inhibitor.
- Compatible with Style 2 Snaps that meet Mil-Spec 10884.
- Grooved design for easy cleaning.
- Tested by marine canvas professionals.
- Withstands pressures 0.6 to 1.0 bar for 5 minutes.
- Does not penetrate a substrate.
- Can be made from a selection of resins and VHB adhesives.
- Stud or socket versions available.

Benefits:

- Provides secure attachment without damaging surface.
- Misplacements easily corrected.
- Documented performance adhesive for marine use.
- Conforms to marine non-slip deck patterns.
- Will not hurt to walk or sit on.
- Prevents corrosion, discoloring or cracking.
- Works with the snaps you are now using.
- Ensures consistent snap action over repeated use.
- Confidence in using best new snap idea in years.
- Used to replace existing studs without extra work.
- Expands applications for RIB's and thin wall construction.
- Versatility in appearance and application.
- New design freedom for canvas, cushions, and carpeting.

Basic Specifications:

Part	Part #	Diameter	O/A Height	Material	Color	Adhesive
Domed Socket 	PG1-0000-839	40mm 1 9/16"	5.3 mm 7/32"	UV Acetal	White	VHB 4941 Conformable 45 mils (1.1mm) 3/64" Gray
Domed Stud 	PG3-0000-839	40mm 1 9/16"	6.5 mm 1/4"	UV Acetal	White	VHB 4941 Conformable 45 mils (1.1mm) 3/64" Gray

Surface Preparation Instructions and Application Guidelines

Snap components will adhere to most clean, dry and well-unified surfaces. Typical surface cleaning solvents are a 50/50 isopropyl Alcohol (rubbing alcohol) water mixture.

Application Pressure:

Bond strength is dependent upon the amount of adhesive-to-surface contact developed. Firm application pressure develops a better adhesive contact and thus improves bond strength.

Application Temperature:

Ideal tape application temperature range is 70°F to 100°F (21°C to 38°C).

Dwell Time

After application, the bond strength increases and approaches the ultimate bond strength after 72 hours at 70°F (21°C). Typical bond strength build-up: 20 minutes equals 50% bond strength, one hour equals 75% bond strength, one day equals 90% bond strength, and three days equals 100% bond strength.

ORDER TOLL FREE

TOLL FREE 1-877-322-6544
LOCAL 1-973-249-0430
FAX 1-973-546-4112
WEB excelsewingsupply.com